

Features Description

- Solar Powered**
 The transmitting module employs a solar panel to generate power, which is stored in a lithium battery.
- Wireless Digital Communication**
 The wireless load cell uses a 2.4GHz wireless digital communication protocol to generate a transmission wirelessly.
- U-Shaped Structure**
 The transmitting module's U-shaped design provides for easy installation, repair, and maintenance.
- Standard Output**
 The receiving module output generates a standard 4-20mA or 0-10mV signal. By providing a standard output this wireless load cell can easily be used to replace a conventional load cell.



Technical Data		
ITEM	TECHNICAL PARAMETERS	UNIT
Analog outputs	4-20	mA
	0-10	mV
Receiving module power supply	9~36	VDC
Range	0~50,000	LBS
Allowed overload	150	%
Precision	0.5	%
Communication distance	50	m
Communication frequency	2.4	GHz
Transmitting power	0	dBm
Insulation resistance	≥2000	MΩ
Operating temperature	-20~+60	°C
Storage temperature	-20~+60	°C
IP grade	IP67	/

Bright Automation is an energy industry leader in electronic monitoring and control products and systems, offering a broad range of advanced drilling products – including VFDs, SCRs, top drive control systems, and auto-drilling systems – in addition to its industry-leading line of lift control systems.